

## ► Double-acting Aluminum Cylinder

- Light weight;
- These double acting cylinders enable quick retraction and are designed to be used in all orientations;
- 50 ton and larger cylinders have been surface treated for rigidity and have carry handles;
- 20T and 30T cylinders are available on request;
- Over-pressurisation is prevented due to built in safety valves;
- The stop-ring avoids cylinder piston rod over-reaching, accommodating maximum cylinder extension;
- Cylinder piston rod wiper reduces contamination, extending cylinder life;
- Removable hardened saddles protect cylinder piston rod during lifting and pressing.



Model	Capacity (ton)	Stroke (mm)	Max. Capacity (kn)		Oil Capacity		Collaps. Height A (mm)	Outside Dia. D (mm)	Saddle Protr. From Plgr. K (mm)	Weight (kg)
			Push	Pull	Push	Pull				
KSRAR-502	50	50	496	187	354	134	201	145	3	11.1
KSRAR-504		100	496	187	709	267	251	145	3	12.7
KSRAR-506		150	496	187	1063	401	301	145	3	14.3
KSRAR-1004	100	100	1002	557	1431	795	301	185	3	19.3
KSRAR-1006		150	1002	557	2147	1193	351	185	3	24.2
KSRAR-1008		200	1002	557	2863	1590	401	185	3	25.1
KSRAR-1506	150	150	1589	924	3405	1979	348	230	3	33.2

\*More models are available. Please contact sales for details.