

➤ Double-acting Hydraulic Cylinder

- Max Working Pressure: 700 Bar;
- These double acting cylinders enable quick retraction and are designed to be used in all orientations;
- Base mounting holes along with ram and collar threads enable various installation options;
- Unique loading design enables it to bear unbalanced loads up to 3% capacity with no damage to the cylinder;
- The cylinder piston rod is protected from damage by the interchangeable hardened saddles;
- Cylinder piston rod wiper reduces contamination, extending cylinder life;
- Over-pressurisation is prevented due to built in safety valves; Coated with corrosive resistant baked enamel.



Model	Capacity (ton)	Stroke (mm)	Max .Cylinder Capacity (Kn)		Oil Capacity (cm ³)		Bolt Circle (mm)	Collaps. Height A (mm)	Weight (kg)
			Push	Pull	Push	Pull			
KSRR-1010	10	254	101	33	368	122	-	409	12
KSRR-1012		305	101	33	442	147	-	457	14
KSRR-308	30	209	295	53	879	400	-	395	18
KSRR-3014		368	295	53	1549	703	-	549	29
KSRR-506	50	156	498	103	1111	335	-	331	30
KSRR-5013		334	498	103	2378	718	-	509	52
KSRR-5020		511	498	103	3638	1099	76	733	68
KSRR-756	75	156	718	156	1601	490	-	347	41
KSRR-7513		333	718	156	3417	1046	-	525	68
KSRR-1006	95	168	933	435	2238	1045	139	357	61
KSRR-10013		333	933	435	4439	2071	139	524	93
KSRR-10018		460	933	435	6132	2861	139	687	117
KSRR-1502	150	57	1386	668	1129	544	-	196	49
KSRR-1506		156	1386	668	3090	1488	158	385	93
KSRR-15013		333	1386	668	6597	3711	158	582	124
KSRR-15032		815	1386	668	16145	7775	-	1116	238
KSRR-2006	200	152	1995	1017	4332	2209	127	430	147
KSRR-20013		330	1995	1017	9405	4795	127	608	199
KSRR-20018		457	1995	1017	13025	6640	127	165	204
KSRR-20024		610	1995	1017	17385	8863	127	917	279
KSRR-20036		914	1995	1017	26049	13280	127	1222	383
KSRR-20048		1219	1995	1017	34741	17712	127	1527	483
KSRR-3006	325	153	3201	1703	6997	3721	158	485	200
KSRR-30012		305	3201	1703	13947	7418	158	638	312
KSRR-30018		457	3201	1703	20889	11114	158	790	385
KSRR-30024		609	3201	1703	27850	14811	158	943	469
KSRR-30036		915	3201	1703	41843	22253	158	1247	628
KSRR-30048		1219	3201	1703	55745	29646	158	1552	780
KSRR-4006	440	152	4292	2297	9319	4987	203	538	303
KSRR-40012		305	4292	2297	18700	10007	203	690	399
KSRR-40018		457	4292	2297	28018	14995	203	843	453
KSRR-40024		610	4292	2297	37400	20014	203	995	597
KSRR-40036		914	4292	2297	56037	29988	203	1300	792
KSRR-40048		1219	4292	2297	74737	39996	203	1605	980
KSRR-5006	520	153	5108	2838	11164	6203	203	577	432
KSRR-50012		305	5108	2838	22256	12365	203	730	589
KSRR-50018		457	5108	2838	33347	18526	203	882	680
KSRR-50024		609	5108	2838	44440	24689	203	1035	816
KSRR-50036		915	5108	2838	66768	36973	203	1339	1002
KSRR-50048		1219	5108	2838	88951	49418	203	1644	1224